

LMBF(K)···UU 尼龙保持架

该类型轴承采用英制尺寸，主要是美洲采用。

所有型号均可根据客户要求做镀镍处理，有防锈作用。

LMBF(K)···UU (Resin retainer)

This type is a metric dimension series mainly used in the America.

All models can be done with nickle plated according to customers' requirements, with function of rust-proof.



LMBF···UU




LMBK···UU



公称轴径 Nominal shaft diameter inch/mm	圆（方）法兰 LMBF(K)···UU	重量 Weight (g)	主要尺寸和公差 Major dimensions and tolerance					
			dr		D		L	
			Inch/mm	公差 Tolerance Inch/ μ m	Inch/mm	公差 Tolerance Inch/ μ m	Inch/mm	公差 Tolerance Inch/ μ m
1/4 6.350	LMBF4UU LMBK4UU	32 25	.2500 6.350		.5000 12.700	⁰ _{-.00050} ⁰ ₋₁₃	.7500 19.050	
3/8 9.525	LMBF6UU LMBK6UU	47 32	.3750 9.525	0 -.00040	.6250 15.875	0 -.00065	.8750 22.225	
1/2 12.700	LMBF8UU LMBK8UU	88 68	.5000 12.700	0 -9	.8750 22.225	0 -16	1.2500 31.750	
5/8 15.875	LMBF10UU LMBK10UU	140 124	.6250 15.875		1.1250 28.575		1.500 38.100	
3/4 19.050	LMBF12UU LMBK12UU	190 150	.7500 19.050	0 -.00040	1.2500 31.750	0 -.00075	1.6250 41.275	±.012 ± 300
1 25.400	LMBF16UU LMBK16UU	325 280	1.0000 25.400	0 -10	1.5625 39.688	0 -19	2.2500 57.150	
1-1/4 31.750	LMBF20UU LMBK20UU	665 580	1.2500 31.750	0 -.00050	2.0000 50.800	0 -.00090	2.6250 66.675	
1-1/2 38.100	LMBF24UU LMBK24UU	1,100 930	1.5000 38.100	0 -12	2.3750 60.325	0 -22	3.0000 76.200	
2 50.800	LMBF32UU LMBK32UU	1,760 1,580	2.0000 50.800		3.0000 76.200	⁰ _{-.00100} ⁰ ₋₂₅	4.0000 101.600	

密封型 Seal type:

LMBF20 A UU	不标 UU	不带密封 双密封	No entry UU	No seals Seal on both sides
	A	镀镍	A	Nickle plated



LMBF···UU



LMBK···UU

主要尺寸和公差 Major dimensions and tolerance							偏心 Eccentricity Inch/ μ m	垂直度 Squareness Inch/ μ m	额定负荷 Basic load rating	
法兰 Flange									动负荷 Dynamic C N	静负荷 Static Co N
Df Inch/mm	K Inch/mm	t Inch/mm	Dp Inch/mm	X Inch/mm	Y Inch/mm	Z Inch/mm				
1.2500 31.750	1.0000 25.400	.2188 5.556	.8750 22.225	.1560 3.969	.2500 6.350	.1410 3.572	.0005 12	.0005 12	206	265
1.5000 38.100	1.2500 31.750	.2500 6.350	1.0620 26.988	.1875 4.763	.2970 7.541	.1720 4.366			225	314
1.7500 44.450	1.3750 34.925	.2500 6.350	1.3125 33.338	.1875 4.763	.2970 7.541	.1720 4.366			510	784
2.0000 50.800	1.5000 38.100	.2500 6.350	1.5620 39.688	.1875 4.763	.2970 7.541	.1720 4.366			774	1,180
2.1875 55.563	1.6875 42.863	.3125 7.938	1.7188 43.656	.2187 5.556	.3440 8.731	.2030 5.159	.0006 15	.0006 15	862	1,370
2.5000 63.500	2.0000 50.800	.3125 7.938	2.0310 51.594	.2187 5.556	.3440 8.731	.2030 5.159			980	1,570
3.1250 79.375	2.5000 63.500	.3750 9.525	2.5625 65.088	.2812 7.144	.4060 10.319	.2656 6.747	.0008 20	.0008 20	1,570	2,740
3.7500 95.250	3.0000 76.200	.5000 12.700	3.0625 77.788	.3440 8.731	.5000 12.700	.3280 8.334			2,180	4,020
4.3750 111.125	3.5000 88.900	.5000 12.700	3.6875 93.662	.3440 8.731	.5000 12.700	.3280 8.334	.0010 25	.0010 25	3,820	7,940

国际单位: 1N ≈ 0.225lbs
1kg ≈ 2.205lbs
SIUNIT: 1N ≈ 0.225lbs
1kg ≈ 2.205lbs