

LMSHP...UU 尼龙保持架


该类型尺寸是公制的，广泛应用于亚洲和其它国家。

所有型号均可根据客户要求做镀镍处理，有防锈作用。

LMSHP...UU (Resin retainer)

This type is a metric dimension series widely used in Asia and other countries.


All models can be done with nickle plated according to customers' requirements, with function of rust-proof.



LMSHP...UU

公称轴径 Nominal Shaft diameter mm	紧凑型导向 椭圆法兰 LMSHP...UU	重量 Weight (g)	钢球 列数 Ball circuit	主要尺寸和公差 Major dimensions and tolerance					
				dr		D		L	
				mm	公差 Tolerance μ m	mm	公差 Tolerance μ m	mm	公差 Tolerance μ m
6	LMSHP6UU	12.9	6	6	0 -9	10	0	19	± 300
8	LMSHP8UU	20.7		8		13	-13	24	
10	LMSHP10UU	41.9		10		17	0 -16	29	
12	LMSHP12UU	47		12		19		30	0
16	LMSHP16UU	85		16		26		37	-200

密封型 Seal type: LMSHP16 A UU	不标	不带密封	No entry	No seals
	UU	双密封	UU	Seal on both sides
	A	镀镍	A	Nickle plated



主要尺寸和公差 Major dimensions and tolerance										偏心 Eccentricity μ m	垂直度 Squareness μ m	额定负荷 Basic load rating	
法兰 Flange												动负荷 Dynamic C N	静负荷 Static Co N
ℓ mm	Df mm	W mm	t mm	A mm	F mm	X mm	Y mm	Z mm	R mm				
5	25	16	5	19	—	3.5	6	3.1	3	12	12	131	155
5	28	19	5	22	—	3.5	6	3.1	3			235	277
6	35	23	6	27	—	4.5	7.5	4.1	3.75			368	433
6	38	25	6	30	—	4.5	7.5	4.1	3.75			381	449
6	44	32	6	27	24	4.5	7.5	4.1	3.75			608	716

国际单位：1N≈0.102kgf
SIUNIT: 1N≈0.102kgf